

# Oversight



**TOUGH JOB**

**TOUGHER TAPE**





# Anvendelses vejledning HPX Tape

●●● : meget velegnet/highly suitable | ●● : egnet/suitable | ● : moderat egnet/moderately suitable | X : uegnet/unsuitable

DUCT TAPE REPAIRS DUCT TAPES	Side(r) Page(s)	Metal Metal	Plast Plastics	PE/PP PE/PP	Træ Wood	Glas Glass	Sten/Beton Stone/Concrete	Indendørs brug Indoor use	Udendørs brug Outdoor use	UV-resistent UV resistant
HPX 6200 REPAIR TAPE	4, 44	●●●	●●●	●●●	●●●	●	●	●●●	●●●	par dage couple of days
PRO DUCT TAPE ORANGE	4	●●●	●●●	●●●	●●	●	●	●●●	●●●	par dage couple of days
DUCT TAPE 2200	5	●●●	●●●	●●●	●●	●	●	●●●	●●●	par dage couple of days
DUCT TAPE 1900	5	●●●	●●●	●●●	●●	●	●	●●●	●●●	par dage couple of days
GAFFER TAPE MATT BLACK	6	●●●	●●●	●●●	●●●	●	●	●●●	●●●	par dage couple of days
MATT GAFFER TAPE PRO	6	●●●	●●●	●●●	●●●	●	●	●●●	●●●	par dage couple of days
GAFFER TAPE FLUO	7	●●●	●●●	●●●	●●●	●	●	●●●	●●●	par dage couple of days
FLUO GAFFER TAPE PRO	7	●●●	●●●	●●●	●●●	●	●	●●●	●●●	par dage couple of days
GAFFER 6000 TAPE 'SOUND AND LIGHT'	8	●●●	●●●	●●●	●●●	●	●	●●●	●●●	par dage couple of days
ALL WEATHER TAPE	8	●●●	●●●	●●●	●●	●●●	●	●●●	●●●	forlænget prolonged
AGRITAPE	9	●●●	●●●	●●●	●●	●	●	●●●	●●●	forlænget prolonged

MONTERINGSTAPE MOUNTING TAPES	Side(r) Page(s)	Metal Metal	Plast Plastics	PE/PP PE/PP	Træ Wood	Glas Glass	Sten/Beton Stone/Concrete	Indendørs brug Indoor use	Udendørs brug Outdoor use	belastning Load
MAX POWER TRANSPARENT	10	●●●	●●●	X	●●	●●●	X	●●●	●●●	●●●
MAX POWER OUTDOOR	10	●●●	●●●	X	●●	●●●	X	●●●	●●●	●●●
HSA HIGH STRENGTH ACRYLIC 3200	11, 45	●●●	●●●	X	●●	●●●	X	●●●	●●●	●●●
SIDE MOULDING TAPE	11, 46	●●●	●●●	X	●●	●●●	X	●●●	●●●	●●
MIRROR MOUNTING TAPE	12	●●●	●●●	X	●●●	●●●	X	●●●	●●●	●●
DOUBLE SIDED MOUNTING TAPE 3MM	12	●●●	●●●	X	●●●	●●●	X	●●●	●●●	●●
DOUBLE SIDED MOUNTING TAPE	12	●●●	●●●	●●	●●●	●●●	X	●●●	●● (midlertidig/ temporary)	●●
DOUBLE SIDED MOUNTING TAPE BLACK	13	●●●	●●●	X	●●●	●●●	X	●●●	●●●	●●
ULTRA MOUNT TAPE	13, 46	●●●	●●●	X	●●●	●●●	X	●●●	●●●	●●
MULTI TACK DOUBLE SIDED MOUNTING TAPE	14	●●●	●●●	●●●	●●●	●●	●●●	●●●	●●●	●●
MULTI TACK DOUBLE SIDED MOUNTING TAPE - LED PROFILE	14	●●●	●●●	●●●	●●●	●●	●●●	●●●	●●●	●●
DOUBLE SIDED CARPET TAPE	15, 43	●●●	●●●	●	●●●	●●●	X	●●●	●●●	●●●
DOUBLE SIDED TAPE	15	n.a. n.a.	●●●	●●●	●●●	n.a. n.a.	●	●●●	X	X
DOUBLE SIDED TISSUE TAPE	15	●●●	●●●	●●	●●●	●●●	X	●●●	●	X
EXPO CARPET TAPE	16	n.a. n.a.	●●	●●	●●	n.a. n.a.	X	●●●	X	X
EMBLEM PRESS & MOUNT	16	n.a. n.a.	●●●	●●●	●●●	n.a. n.a.	●●	●●●	X	X
ZIP FIX	17, 46	●●	●●	●	X	●●	X	●●●	●●●	●
DUO GRIP	17, 47	●●●	●●●	●	●●●	●	X	●●●	●●●	●●
BACKGRIP	18	●●●	●●●	X	●●●	●●●	X	●●●	●●●	●●



●●● : meget velegnet/highly suitable | ●● : egnet/suitable | ● : moderat egnet/moderately suitable | X : uegnet/unsuitable

TÆTNINGSBÅND SEALING TAPES	Side(r) Page(s)	Metal Metal	Plast Plastics	PE/PP PE/PP	Træ Wood	Glas Glass	Sten/Beton Stone/Concrete	Indendørs brug Indoor use	Udendørs brug Outdoor use
BUTYL SEALING TAPE	19	●●	●●	●	●	●●	●●	●●●	●●●
POWER SEALING TAPE	19	●●●	●●●	●●●	●●	●●●	●●	●●●	●●●
ALUBUTYL	20	●●	●●	●●●	●●●	●●	●●	●●●	●●●

LANGLEBIGE LUFTDICHT PRODUKTE DURABLE AIRTIGHT PRODUCTS	Side(r) Page(s)	Metal Metal	Plast Plastics	PE/PP PE/PP	Træ Wood	Indendørs brug Indoor use	Udendørs brug Outdoor use	Flexibility	Aging resistance Aging resistance
AIRTIGHT FLEX	21	●●●	●●●	●●●	●●●	●●●	●●	●●●	●●●
AIRTIGHT UV	22	●●●	●●●	●●●	●●●	●●●	●●●	●●●	●●●
AIRTIGHT INDOOR	22	●●●	●●●	●●●	●●●	●●●	●	●	●●●
AIRTIGHT ROOF	23	●●●	●●●	●●●	●●●	●●●	●●●	●	●●●
AIRTIGHT FIX	23	●●●	●●●	●●●	●●●	●●●	●	●	●●●

AFDÆKNINGSTAPE MASKING TAPES	Side(r) Page(s)	Metal Metal	Plast Plastics	Træ Wood	Glas Glass	Sten/Beton Stone/Concrete	Indendørs brug Indoor use	Udendørs brug Outdoor use	UV-resistent UV resistant
MASKING TAPES 100°C	24	●●●	●●●	●●●	●●●	●	●●●	●	midlertidig temporary
MASKING TAPES 60°C	24	●●●	●●●	●●●	●●●	●	●●●	●	midlertidig temporary
MASKING 4800 DELICATE SURFACES	25	●●●	●●●	●●●	●●●	X	●●●	●●	4 måneder 4 months
MASKING 4400 FINE LINE	25	●●●	●●●	●●●	●●●	X	●●●	●●●	6 måneder 6 months
MASKING 4900 EXTRA STRONG	26	●●●	●●●	●●●	●●●	●●●	●●●	●●●	6 måneder 6 months
MASKING TAPE UV	26	●●●	●●●	●●●	●●●	●	●●●	●●●	14 dage 14 days
EASY MASK	27	●●●	●●●	●●●	●●●	●	●●●	X	par dage couple of days
EASY MASK FINE LINE	28	●●●	●●●	●●●	●●●	X	●●●	●●●	6 måneder 6 months
EASY MASK OUTDOOR	28	●●●	●●●	●●●	●●●	●●	●●●	●●	par dage couple of days
PRO COVER	29	●●●	●●●	●●●	●●●	●●	●●●	●●●	1 måned 1 month
PVC ORANGE	29	●●●	●●●	●●●	●	●●	●●●	●●	par dage couple of days
CLEAN REMOVAL TAPE	29	●●●	●●●	●●●	X	●●●	●●●	X	par dage couple of days
PVC FORM WORK TAPE	30	●●●	●●●	●●●	●	●●●	●●●	●●●	par dage couple of days
TRIM MASKING TAPE	30	●●●	●●●	X	●●●	X	●●●	X	n.a. n.a.
FINE LINE TAPE	30	●●●	●●●	●●●	●●●	X	●●●	X	n.a. n.a.



●●● : meget velegnet/highly suitable | ●● : egnet/suitable | ● : moderat egnet/moderately suitable | X : uegnet/unsuitable

SIKKERHED OG MÆRKNING SAFETY AND MARKING	Side(r) Page(s)	Glatte overflader Smooth surfaces	Porøse overflader Porous surfaces	Indendørs brug Indoor use	Udendørs brug Outdoor use
SAFETY TAPE	31	●●●	●	●●●	●●●
SAFETY TEXTILE TAPE	31	●●●	●	●●●	●●
HEAVY DUTY MARKING TAPE	31	●●●	●	●●●	●●●
LANE MARKING TAPE	32	●●●	●	●●●	●●●
BARRIER TAPE	32	n.a. n.a.	n.a. n.a.	●●●	●●●
SUPER BARRIER TAPE	32	n.a. n.a.	n.a. n.a.	●●●	●●●
SAFETY GRIP	33	●●●	●	●●●	●●●
AQUA GRIP	33	●●●	●	●●●	●●●

SPECIALPRODUKTER SPECIALTIES	Side(r) Page(s)	Metal Metal	Plast Plastics	PE/PP PE/PP	Træ Wood	Glas Glass	Sten/Beton Stone/Concrete	Indendørs brug Indoor use	Udendørs brug Outdoor use
CAR PAINT PROTECTION FILM	34	●●●	●●	X	X	●●●	X	●●●	●●●
BLACK PROTECTION FILM	34	●●●	●●	X	X	●●●	X	●●●	●●●
ALU TAPE	35, 47	●●●	●●●	●	●	X	X	●●●	●●●
DRYWALL JOINTING TAPE	35	●●●	●●	●	●●	n.a. n.a.	n.a. n.a.	●●●	●

ISOLERINGSTAPE INSULATING TAPES	Side(r) Page(s)	Tykkelse Thickness	Gennemslagsspænding Breakdown voltage	Maks. temperatur Maximum temperature	Brandhæmmende Flame retardant	Trykklasse Pressure class	Indendørs brug Indoor use	Udendørs brug Outdoor use
INSULATION TAPE 5200	36, 48	0,15 mm	6 kV	+80°C	ja yes	n.a. n.a.	●●●	●●●
INSULATION TAPE 52100	37	0,15 mm	6 kV	+90°C	ja yes	n.a. n.a.	●●●	●●●
INSULATION TAPE 52300	37	0,12 mm	5 kV	+80°C	ja yes	n.a. n.a.	●●●	●●●
INSULATION TAPE 52400	38	0,19 mm	7 kV	+80°C	ja yes	n.a. n.a.	●●●	●●●
PTFE TAPE GAS	38	0,10 mm	n.a. n.a.	+260°C	n.a. n.a.	0,2 bar	●●●	●●●
PTFE TAPE WATER	38	0,10 mm	n.a. n.a.	+260°C	n.a. n.a.	n.a. n.a.	●●●	●●●
SELF FUSION TAPE	39, 48	0,50 mm	21 kV	+90°C	n.a. n.a.	n.a. n.a.	●●●	●
STRETCH & FUSE	39	0,50 mm	8 kV	+200°C (midlertidig/ temporary: +260°C)	n.a. n.a.	8 bar	●●●	●●●
CABLE PROTECTION TAPE	40,48	0,30 mm	n.a. n.a.	+105°C	n.a. n.a.	n.a. n.a.	●●●	X
CLOTH INSULATION	40	0,25 mm	n.a. n.a.	+105°C	n.a. n.a.	n.a. n.a.	●●●	X